

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number
WO 03/087546 A1

(51) International Patent Classification⁷: **F01M 1/18**,
F02D 41/22, F16N 29/04

(21) International Application Number: PCT/SE03/00563

(22) International Filing Date: 8 April 2003 (08.04.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0201066-8 9 April 2002 (09.04.2002) SE

(71) Applicant and

(72) Inventor: **PERSSON, Leif** [SE/US]; 727 81st Street,
Downers Grove, IL 60516 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT (util-
ity model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,

CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (util-
ity model), DE, DK (utility model), DK, DM, DZ, EC, EE
(utility model), EE, ES, FI (utility model), FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ,
LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU,
SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: SYSTEM AND METHOD FOR DETECTING LUBRICANT IN THE FUEL OF AN INTERNAL COMBUSTION ENGINE



(57) Abstract: A system for an internal combustion engine (10) arranged for being powered with a fuel mixed with a lubricant, which system includes:- a detector (16) arranged for detecting the presence of a given additive in the lubricant mixed fuel- an electronic module (24) arranged for comparing the detected presence of the additive with a predetermined threshold value, and designed so that if the lubricant is not mixed in the fuel, or has been mixed in the fuel in an amount lower than a through the additive against the threshold value correlated amount, by means of an indicator (30) indicate that a lack of lubricant is at hand in the fuel and/or by means of a connection (26) to an ignition or injection system (11) for the engine (10) prevent or modify the operation of the internal combustion engine if said lack of lubricant is at hand in the fuel. The invention also refers to the method of how the system operates.

WO 03/087546 A1